



LIQUIP SALES (QLD) PTY. LTD.

ABN 77 011 046 469

730 MACARTHUR AVE
CENTRAL, PINKENBA, Q, 4008
PHONE: (07) 3633-9100
FAX: (07) 3260-1732
jim@liquip-qld.com.au
www.liquip-qld.com.au

SELF BUNDED TANK SPECIFICATIONS

CLASSIC (12,000L - 110,000L)

- Certified to Meet AS1940, AS1692, and AS1657
- Standard I.S.O container hold down pins
- Able to be stacked four high when empty
- Lockable bund area with container style doors
- Electronic overfill alarm
- Hydraulic overfill valve allowing maximum SFL at high flow rate
- Fill line fitted with
 - 3"Camlok fittings
 - Stainless Steel ball valve
 - Stainless steel check valve
- Suction piping fitted with
 - Stainless ball valve
 - Anti-siphon valve
- Sloping floor internally with water well
- Dedicated suction pipe to allow removal of water
- All internal sheets are sandblasted and oiled to prevent corrosion
- Advanced tank design with bottom of tank clear of the ground
- Radius corners to enable inspection under the tank
- Sloping roof to ensure water does not pool on the roof surface
- All fittings are galvanized
- All fasteners are stainless steel
- All socket plugs are Stainless steel
- Calibrated anodised dip stick
- Emergency vent on interstitial space
- Anodised dip stick for interstitial space
- Provision for fitting two high hose masts
- Galvanised ladder that complies with AS1657
- Ladder can be located on either side.
- Air vents on sides of bund to prevent moisture build up.
- Bund area has internal mounting flanges on both wall and floor
- Sockets on sides of bund area to allow for electrical connections
- Two earthing points (one front and one rear)

